



## Safety Data Sheet

**24 Hour Emergency Phone Numbers**  
**Medical/Poison Control:**  
 In U.S.: Call 1-800-222-1222

**Outside U.S.: Call your local poison control center**

**Transportation/National Response Center:**

**1-800-535-5053**  
**1-352-323-3500**

NOTE: The National Response Center emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals.

IMPORTANT: Provide this information to employees, customers, and users of this product. Read this SDS before handling or disposing of this product. This product is covered by the OSHA Hazard Communication Standard and this document has been prepared in accordance with requirements of this standard. All abbreviated terms used in this SDS are further described in Section 16.

### 1. Identification

<b>Product Name:</b>	Weldwood Floor Tile Adhesive	<b>Revision Date:</b>	3/5/2019
<b>Product UPC Number:</b>	070798001398, 070798001374, 070798001367	<b>Supercedes Date:</b>	11/9/2018
<b>Manufacturer:</b>	DAP Products Inc. 2400 Boston Street Suite 200 Baltimore, MD 21224-4723 888-327-8477 (non - emergency matters)	<b>Product Use/Class:</b>	Construction Adhesive
	SDS Coordinator: MSDS@dap.com	<b>SDS No:</b>	00077272001
	Emergency Telephone: 1-800-535-5053, 1-352-323-3500, 1-800-222-1222	<b>Preparer:</b>	Regulatory and Environmental Affairs

### 2. Hazards Identification

#### GHS Classification

Not a hazardous substance or mixture.

#### Symbol(s) of Product

None

#### Signal Word

Not a hazardous substance or mixture.

#### Possible Hazards

43% of the mixture consists of ingredients of unknown acute toxicity

### 3. Composition/Information on Ingredients

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt. %</u>	<u>GHS Symbols</u>	<u>GHS Statements</u>
Petroleum hydrocarbon oil	64742-52-5	10-30	No Information	No Information
Butadiene-styrene copolymer	9003-55-8	7-13	No Information	No Information
Clay	1332-58-7	3-7	No Information	No Information

Poly(oxy-1,2-ethanediyl), alpha(4-nonylphenyl) omega- hydroxy, branched	127087-87-0	1-5 GHS07	H302-332
Urea	57-13-6	1-5 No Information	No Information
Ethylene glycol	107-21-1	1-5 GHS07	H332
Titanium dioxide	13463-67-7	0.1-1.0 GHS07-GHS08	H335-351

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

#### 4. First-aid Measures

**FIRST AID - INHALATION:** If inhaled, remove to fresh air. If breathing is difficult, leave the area to obtain fresh air. If continued breathing difficulty is experienced, get medical attention immediately.

**FIRST AID - SKIN CONTACT:** Remove and wash contaminated clothing. Wash off immediately with soap and plenty of water for at least 15 minutes. Get medical aid if symptoms persist.

**FIRST AID - EYE CONTACT:** In case of contact, immediately flush eyes with large quantities of water for at least 15 minutes until irritation subsides. Get medical attention immediately.

**FIRST AID - INGESTION:** If swallowed, DO NOT INDUCE VOMITING. Get medical attention immediately.

#### 5. Fire-fighting Measures

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** No special protective measures against fire required.

**SPECIAL FIREFIGHTING PROCEDURES:** Wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear. Use water spray to cool exposed surfaces.

**EXTINGUISHING MEDIA:** Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam, Water Fog

#### 6. Accidental Release Measures

**ENVIRONMENTAL MEASURES:** No Information

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** Contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Use personal protective equipment as necessary. In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations. Scrape up dried material and place into containers.

#### 7. Handling and Storage

**HANDLING:** KEEP OUT OF REACH OF CHILDREN! DO NOT TAKE INTERNALLY. Avoid breathing vapor and contact with eyes, skin and clothing. Use only with adequate ventilation. Open all windows and doors or use other means to ensure cross-ventilation and fresh air entry during application and drying. Odor is not an adequate warning for hazardous conditions. Wash thoroughly after handling.

**STORAGE:** Close container after each use. Do not store at temperatures above 120 degrees F. Store containers away from excessive heat and freezing. Store away from caustics and oxidizers.

#### 8. Exposure Controls/Personal Protection

##### Ingredients with Occupational Exposure Limits

<u>Chemical Name</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH-TL STEL</u>	<u>OSHA PEL-TWA</u>	<u>OSHA PEL-CEILING</u>
Petroleum hydrocarbon oil	N.E.	N.E.	N.E.	N.E.
Butadiene-styrene copolymer	N.E.	N.E.	N.E.	N.E.
Clay	2 mg/m3 TWA particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter	N.E.	15 mg/m3 TWA total dust, 5 mg/m3 TWA respirable fraction	N.E.
Poly(oxy-1,2-ethanediyl), alpha(4-nonylphenyl) omega- hydroxy, branched	N.E.	N.E.	N.E.	N.E.
Urea	N.E.	N.E.	N.E.	N.E.
Ethylene glycol	25 ppm TWA vapor fraction	50 ppm STEL vapor fraction, 10 mg/m3 STEL inhalable particulate matter, aerosol only	N.E.	N.E.

Titanium dioxide

10 mg/m3 TWA N.E.

15 mg/m3 TWA N.E.  
total dust

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation  
Sk = Skin Sensitizer N.E. = Not Established

## Personal Protection



**RESPIRATORY PROTECTION:** No personal respiratory protective equipment normally required. A NIOSH-approved air purifying respirator with an organic vapor cartridge or canister may be necessary under certain circumstances where airborne concentrations are expected to exceed exposure limits. In case of insufficient ventilation, wear suitable respiratory equipment. A respiratory protection program that meets the OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.



**SKIN PROTECTION:** Rubber gloves.



**EYE PROTECTION:** Goggles or safety glasses with side shields.



**OTHER PROTECTIVE EQUIPMENT:** Not required under normal use.



**HYGIENIC PRACTICES:** Wash hands before breaks and at the end of workday. Remove and wash contaminated clothing before re-use.

## 9. Physical and Chemical Properties

<b>Appearance:</b>	White	<b>Physical State:</b>	Paste
<b>Odor:</b>	Slight	<b>Odor Threshold:</b>	Not Established
<b>Density, g/cm3:</b>	1.04 - 1.04	<b>pH:</b>	Between 7.0 and 12.0
<b>Freeze Point, °C:</b>	Not Established	<b>Viscosity (mPa.s):</b>	Not Established
<b>Solubility in Water:</b>	No Information	<b>Partition Coeff., n-octanol/water:</b>	Not Established
<b>Decomposition Temperature, °C:</b>	Not Established	<b>Explosive Limits, %:</b>	N.E. - N.E.
<b>Boiling Range, °C:</b>	100 - 100	<b>Auto-Ignition Temperature, °C</b>	Not Established
<b>Minimum Flash Point, °C:</b>	100	<b>Vapor Pressure, mmHg:</b>	Not Established
<b>Evaporation Rate:</b>	Slower Than n-Butyl Acetate	<b>Flash Method:</b>	Seta Closed Cup
<b>Vapor Density:</b>	Heavier Than Air	<b>Flammability, NFPA:</b>	Non-Flammable
<b>Combustible Dust:</b>	Does not support combustion		

(See "Other information" Section for abbreviation legend)

(If product is an aerosol, the flash point stated above is that of the propellant.)

## 10. Stability and Reactivity

**STABILITY:** Stable under recommended storage conditions.

**CONDITIONS TO AVOID:** Excessive heat and freezing.

**INCOMPATIBILITY:** Incompatible with strong bases and oxidizing agents.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Normal decomposition products, i.e., COx, NOx.

## 11. Toxicological Information

**EFFECT OF OVEREXPOSURE - INHALATION:** May be harmful if inhaled. Inhalation may cause irritation to the respiratory tract (nose, mouth, mucous membranes).

**EFFECT OF OVEREXPOSURE - SKIN CONTACT:** Harmful if absorbed through the skin. Prolonged or repeated contact with skin may cause mild irritation.

**EFFECT OF OVEREXPOSURE - EYE CONTACT:** May cause eye irritation. Signs and symptoms may include: pain, tears, swelling, redness and blurred vision. May cause eye irritation of susceptible persons.

**EFFECT OF OVEREXPOSURE - INGESTION:** Harmful if swallowed. Ingestion of ethylene glycol can cause gastrointestinal irritation, nausea, vomiting, diarrhea and if ingested in sufficient quantities, death.

**CARCINOGENICITY:** No Information

**EFFECT OF OVEREXPOSURE - CHRONIC HAZARDS:** Prolonged and repeated skin contact may cause irritation and possibly dermatitis. Repeated or prolonged exposure may cause skin, respiratory, kidney and liver damage. Ethylene Glycol may cause kidney and liver damage upon prolonged and repeated overexposures. Studies have shown that repeated inhalation of ethylene glycol has produced adverse cardiovascular changes in laboratory animals. Ethylene glycol has been shown to cause birth defects in laboratory animals.

**PRIMARY ROUTE(S) OF ENTRY:** Skin Contact, Inhalation

### Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
64742-52-5	Petroleum hydrocarbon oil	5000 mg/kg Rat	5000 mg/kg Rabbit	< 5.7 mg/L Rat
9003-55-8	Butadiene-styrene copolymer	N.I.	N.I.	N.I.
1332-58-7	Clay	>5000 mg/kg Rat	>5000 mg/kg Rat	N.I.
127087-87-0	Poly(oxy-1,2-ethanediyl), alpha(4-nonylphenyl) omega- hydroxy, branched	1310 mg/kg Rat	>2000 mg/kg Rabbit	N.I.
57-13-6	Urea	8471 mg/kg Rat	N.I.	N.I.
107-21-1	Ethylene glycol	4700 mg/kg Rat	9530 mg/kg Rabbit	N.I.
13463-67-7	Titanium dioxide	>10000 mg/kg Rat	>5000 mg/kg Rabbit	>20 mg/L

N.I. = No Information

## 12. Ecological Information

**ECOLOGICAL INFORMATION:** Ecological injuries are not known or expected under normal use.

## 13. Disposal Information

**DISPOSAL INFORMATION:** This product does not meet the definition of a hazardous waste according to U.S. EPA Hazardous Waste Management Regulation, 40 CFR Section 261. Dispose as hazardous waste according to all local, state, federal and provincial regulations. Dispose of material in accordance with all federal, state and local regulations. State and Local regulations/restrictions are complex and may differ from Federal regulations. Responsibility for proper waste disposal is with the owner of the waste.

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** Contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Use personal protective equipment as necessary. In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations. Scrape up dried material and place into containers.

## 14. Transport Information

DOT UN/NA Number:	N.A.
DOT Proper Shipping Name:	Not Regulated
DOT Technical Name:	N.A.
DOT Hazard Class:	N.A.
Hazard SubClass:	N.A.
Packing Group:	N.A.

## 15. Regulatory Information

### SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

### TOXIC SUBSTANCES CONTROL ACT:

All ingredients in this product are either on TSCA inventory list, or otherwise exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

## 16. Other Information

**Revision Date:** 3/5/2019 **Supersedes Date:** 11/9/2018

**Reason for revision:** Product Composition Changed  
 Substance and/or Product Properties Changed in Section(s):  
 05 - Flammability Information  
 08 - Exposure Controls/Personal Protection  
 09 - Physical & Chemical Information  
 11 - Toxicological Information  
 16 - Other Information  
 Substance Chemical Name Changed  
 Substance Hazardous Flag Changed  
 Substance Hazard Threshold % Changed  
 Substance Regulatory CAS Number Changed  
 Revision Statement(s) Changed

**Datasheet produced by:** Regulatory Department

### HMIS Ratings:

Health:	Flammability:	Reactivity:	Personal Protection:
1	0	0	X

VOC Less Water Less Exempt Solvent, g/L: 26.3

VOC Material, g/L: 16

VOC as Defined by California Consumer Product Regulation, Wt/Wt%: 0.19

VOC Actual, Wt/Wt%: 1.6

### Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H302	Harmful if swallowed.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.

### Icons for GHS Pictograms shown in Section 3 describing each ingredient:

GHS07



**GHS08**

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

DAP believes the data and statements contained herein are accurate as of the date hereof. They are offered in good faith as typical values and not as a product specification. NO WARRANTY OF MERCHANTABILITY, WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE WITH REGARD TO THE INFORMATION HEREIN PROVIDED OR THE PRODUCT TO WHICH THE INFORMATION REFERS. Since this document is intended only as a guide to the appropriate use and precautionary handling of the referenced product by a properly trained person, it is therefore the responsibility of the user to (i) review the recommendations with due consideration for the specific context of the intended use and (ii) determine if they are appropriate.