



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® DYNAGRIP® All Purpose Construction Adhesive

PRODUCT DESCRIPTION

DAP® DYNAGRIP® All PURPOSE construction adhesive is a premium grade adhesive ideal for paneling, interior remodeling, and other interior projects. DYNAGRIP® ALL PURPOSE adhesive delivers a strong permanent bond and excellent adhesion on common building materials. Offering easy water cleanup and instant grab, this adhesive delivers the perfect combination of convenience and performance for interior projects.



PACKAGING	COLOR	UPC
5 fl oz (147mL)	Off White	7079827500
10.3 fl oz (305 mL)	Off White	7079827501
28 fl oz (828 mL)	Off White	7079827502

KEY FEATURES & BENEFITS

- **Multi-Material - Strong adhesion to common building materials**
- **Instant Grab – Reduces nailing, bracing & clamping for interior projects**
- **Strong Permanent Bond – Provides a long-lasting bond**

PERFORMANCE CHARACTERISTICS

- Easy water clean up
- Low odor
- Easy to gun
- VOC compliant
- Meets ASTM C557 specification for the installation of drywall panels



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

SUGGESTED USES

Adheres to:

- ABS
- Ceramic Tiles
- Concrete
- Cove Base
- Dimensional Lumber
- Drywall
- Foamboard
- FRP
- Masonry
- OSB
- Polystyrene
- Plywood
- Wood

Recommended for:

- Tub Surround Installation
- Foam Insulation Panels
- Drywall & Decorative Paneling installations
- Molding & Decorative Trim

Not Recommended for:

- Bonding two non-porous materials
- Constant water exposure
- Exterior use
- Flooring applications
- Mirror installation
- Subfloor or deck installation

FOR BEST RESULTS

- Apply in temperatures above 40°F. Keep adhesive above 40°F for easier gunning.
- For square surfaces apply around perimeter and “X” shaped bead.
- For long surfaces use “S” shaped bead.
- Press firmly into place.
- One surface must be porous.
- Store away from extreme heat or cold.

APPLICATION

1. Surfaces must be clean, structurally sound and free of debris.
2. Precut & fit materials before applying adhesive.
3. Trim nozzle to desired bead size ¼” bead recommended for most applications.
4. Puncture inner foil seal.
5. Load into applicator gun.
6. Apply a continuous bead to surface.
7. Within 20 minutes, position & press substrates firmly into place.
8. Certain applications may require mechanical fasteners.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

9. Allow to dry for 24 hours.

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Typical Uncured Physical Properties	
Appearance/Consistency	Smooth paste
Base Polymer:	Acrylic latex
Bead Color	Off white
Weight % Solids	72%
Odor	Mild
Clean Up	Soap & water
Flash Point	212°F
Shelf Life	18 months
Coverage	10oz: ¼" bead yields 32 linear ft, 3/8" bead yields 14 linear ft 28oz: ¼" bead yields 86 linear ft, 3/8" beach yields 38 linear ft
Typical Application Properties	
Application Temperature Range:	40°F – 100°F
Tooling Time (Working Time)	20 minutes
Full Cure Time	7 days
Typical Cured Performance Properties	
Service Temperature Range:	40°F – 100°F
Gap Bridging	N/A
VOC Content	< 15g/L
Calif. ARB VOC	<0.5% Wt/Wt

CLEAN UP & STORAGE

Uncured adhesive: wash away with warm water and soap. Cured adhesive: must be cut or scraped away.

SAFETY



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at dap.com or by calling **1-888-DAP-TIPS**.

WARRANTY

DAP will provide replacement product or refund sales price if product fails to perform when used as directed. Call 1-888-DAP-TIPS, with your sales receipt and product container available, to arrange for warranty fulfillment. DAP is not liable for incidental or consequential damages.

COMPANY IDENTIFICATION

Manufacturer: DAP Products Inc., 2400 Boston Street, Baltimore, Maryland 21224

Usage Information: Call **1-888-DAP-TIPS** or visit dap.com & click on "Ask the Expert"

Order Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com