



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® BLUE STIK™ Reusable Adhesive Putty

PRODUCT DESCRIPTION

DAP® Blue Stik™ is a reusable, removable adhesive putty that replaces tape, tacks, staples and magnets. It is ideal for a wide variety of uses in the home, school and office. It can be used time and time again and won't dry out. No more chipped, peeled paint or holes in the walls. This convenient, ready-to-use putty bonds just about anything to slick or hard surfaces, such as wood, tile, glass, concrete, porcelain, Formica®, metal and painted surfaces. Use to fasten decorations, posters, notes and paintings. Also helps protect items from vibration damage. Blue Stik™ can be used time and time again. Conforms to ASTM D 4236.



| PACKAGING | COLOR | UPC |
|---------------|-------|------------|
| 1.0 oz (28 g) | Blue | 7079801201 |

KEY FEATURES & BENEFITS

- **Replaces tape & tacks**
- **Removable**
- **No mess**
- **Non-toxic**
- **For hanging posters, photos & drawings**

SUGGESTED USES

Ideal for all types of hobby and craft, school, office and around the home uses.

- Level picture hanging picture frames.
- Secure collectibles.
- Keep cords and cables in place.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

- Hold needles.
- Hold hooks and fishing lures.
- Temporarily hold items in place while liquid glue dries.

Use to mount or hang:

- Posters
- Photos
- Drawings
- Cards
- Decorations
- Notes

Adheres to a wide variety of surfaces such as:

- Wood
- Tile
- Glass
- Concrete
- Porcelain
- Formica®
- Metal
- Paper
- Styrofoam
- Plastic
- Vinyl
- Plastic laminate
- Fabrics
- Painted surfaces

APPLICATION

1. DAP® Blue Stik™ should be applied to clean, dry surfaces at room temperature (68-72°F, 21-23°C).
2. To use, tear off enough Blue Stik™ Reusable Adhesive Putty for the job.
3. Roll into a ball until it becomes soft and tacky.
4. Place adhesive between the surfaces to be fastened and press firmly.
5. **CAUTION:** Blue Stik™ may leave an oily residue on some surfaces (e.g. flat latex painted drywall). Check by applying Blue Stik™ in an inconspicuous place for 24 hours, then lift.
6. If a stain does occur, it can usually be removed with Isopropyl (rubbing) alcohol. Do not use Blue Stik™ on soft flocked or loose wallpaper, newly painted surfaces, loose paint, or for hanging heavy objects such as mirrors and framed pictures. Not for exterior applications. If Blue Stik™ residue should remain on surface, roll Blue Stik® into a ball and roll over residue.

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

| | |
|----------------|-------------|
| Vehicle: | Rubber |
| Consistency: | Pliable |
| Solids: | >99% Weight |
| Weight/Gallon: | 7.4lbs/gal |
| Color: | Blue |



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

| | |
|-----------------------|-----------------|
| Odor: | Negligible |
| Freeze/Thaw Stability | Stable |
| Shelf Life: | 1 Year, minimum |

CLEAN UP & STORAGE

This product may leave an oily residue on some surfaces. Prior to use, check by applying product in an inconspicuous place for 24 hours, then remove. If a stain does occur, it can usually be removed with a solvent like Isopropyl (rubbing alcohol). If Blue Stik™ residue should remain on surface, roll Blue Stik™ into a ball and roll over residue.

SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at dap.com or by calling **1-888-DAP-TIPS**.

WARRANTY

If you are not satisfied with this product's performance when used as directed, return used container and sales receipt to DAP Products Inc., Technical Customer Service, 2400 Boston Street, Suite 200, Baltimore, MD 21224 for product replacement or sales price refund. DAP will not be liable for incidental or consequential damages.

COMPANY IDENTIFICATION

Manufacturer: DAP Products Inc., 2400 Boston Street, Baltimore, Maryland 21224

Usage Information: Call **1-888-DAP-TIPS** or visit dap.com & click on "Ask the Expert"

Order Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com